

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (Currently Amended) A method for packaging flat objects (4), the method comprising the steps of:  
    ~~Continuously~~continuously forming a quasi-endless web of a packaging material (7) into a string of bags (7') ~~being that are~~ open on three sides and closed on one side, and  
    conveying the string of bags in a conveying direction,  
    during conveyance, charging each of the bags (7') with at least one flat object (4)~~each~~,  
    severing the bags (7') from the string of bags, and  
    sealing the bags (7') by seams corresponding to the open bag sides, wherein, during all method steps, an open side of the bags opposite to the one closed side and a corresponding seam keep a position ~~which that~~ is independent of ~~the a~~ format of the object to be packaged (4), and  
    wherein, at least one of in the step of forming the string of bags, a depth of the bags (7'), in the step of forming the string of bags, and/or, and a distance between two seams corresponding to lateral open sides of the bag, in the step of sealing the bags, ~~a distance between two seams corresponding to lateral open sides of the bag~~ are adjusted to one of the format of the object to be packaged (4), or to the width of the packaging material respectively.
2. (Currently Amended) The method according to claim 1, wherein the bags (7') are charged from above through the one open side opposite the one closed side and are secured in ~~the an~~ area of said open side from before the steps of charging and severing to the step of sealing.

3. (Currently Amended) The method according to claim 1, wherein the bags (7') are sealed while being positioned in conveying compartments (3) rotating in the conveying direction, wherein the bags (7') are formed in or supplied to the conveying compartments (3), ~~or are supplied to the conveying compartments,~~ and wherein the bags are charged with the objects to be packaged (4) in the conveying compartments (3) or before the bags are supplied to the conveying compartments (3).
4. (Currently Amended) The method according to claim 3, comprising the further steps of drawing ~~wherein~~ the packaging material (7) to be formed into a string of bags is ~~drawn~~ into the rotating conveying compartments (3) by a plurality of drawing-in members (8.2), and ~~wherein~~, in the conveying compartment (3), securing each fully formed bag (7') is secured in the a region of its open side opposite its one closed side, and then wherein withdrawing the drawing-in member (8.2) ~~is then withdrawn~~ from the bag, wherein the length of the drawing-in member (8.2) determines the depth of the bag (7').
5. (Currently Amended) The method according to claim 3, comprising the further steps of forming ~~wherein~~ the string of bags is ~~formed~~ from the packaging material (7) by guides (8.7, 8.8) acting alternately from either side of the packaging material, said which guides (8.7, 8.8) being ~~are~~ driven to move in the conveying direction and to be spaced, distanced relative to each other transverse to the conveying direction, at a distance measure ~~adjusted~~ to the depth of the bags to be formed, and securing wherein the bags (7') are ~~secured~~ to alternate guides (8.7), are then charged ~~charging the bags~~ with objects (4) and are then, for being sealed, positioned ~~positioning the bags~~ in rotating conveying compartments (3) for sealing.
6. (Currently Amended) The method according to claim 1, wherein the packaging material (7) is a weldable plastic foil or sheet material and wherein sealing of the bags is ~~effected~~ accomplished by welding.

7. (Currently Amended) A device for packaging flat objects (4) using a packaging material (7) in the shape of a quasi-endless web, the device comprising:
- means (5, 9) for supplying objects to be packaged (4) and for removing packaged objects (4'),
  - a-means (6) for supplying the packaging material (7),
  - a-means for forming, from the packaging material (7), a string of bags (7') being that are open on three sides and closed on one side,
  - a-means for conveying the bags (7') in a conveying direction,
  - a-means for severing the bags (7') from the string of bags, and
  - a-means for sealing the open sides of the bags (7') by producing appropriate seams,
- wherein the means for forming the bags (7') and the means for conveying the bags (7') are arranged ~~in such a way~~such that the open side opposite the one closed side of the bags and the corresponding seam keep an unchanged position independent of the format of the object to be packaged (4), and
- wherein at least one of the means for forming the string of bags (7'), which adjusts a depth of the bags, and ~~is adjustable for adjusting a depth of the bags and/or the means for sealing the bags (7'), which adjusts a distance between two lateral seams,~~ is adjustable ~~for adjusting the distance between two lateral seams.~~
8. (Currently Amended) The device according to claim 7, wherein the means for conveying the bags (7') is designed and arranged ~~in such a manner that,~~ at least at a point of supply of the objects to be packaged (4), the bags (7') are positioned with their open side opposite the one closed side facing upwards, and wherein the conveying means is equipped with securing elements (22, 27) ~~being equipped for securing the bags (7') in the region of said open side~~ opposite the one closed side.
9. (Currently Amended) The device according to claim 7, wherein the means for forming the string of bags (7') comprises drawing-in members (8.2) of an

adjustable length and ~~co-operating~~cooperating with distal ends of rotating compartment elements (2), and wherein the securing elements (22) are arranged in conveying compartments (3) formed by the compartment elements (2).

10. (Currently Amended) The device according to claim 9, wherein ~~the~~ distal ends of the rotating compartment elements (2) and of the drawing-in members (2.1) comprise freely rotating rollers (2.1).
11. (Currently Amended) The device according to claims 7, wherein the means for forming the string of bags (7') comprises circulating guides (8.7, 8.8); wherein the guides are adapted ~~equipped for to~~ alternately acting-act from two opposing sides of the packaging material (7) and to be displaced relative to each other and transversely to a circulation direction, and wherein each alternate guide (8.7) is equipped with securing elements (27).
12. (Currently Amended) The device according to claim 11, wherein a circulation path of the guides (8.7) is aligned with a rotation path of the conveying compartments (3) such that the guides (8.7) are conveyed along a part of their path in ~~the~~ a region of the distal ends of the compartment elements (2) ~~which-that~~ form the conveying compartments (3).
13. (Currently Amended) The device according to claim 7, wherein the rotating conveying compartments (3) are equipped with sealing elements (21.1, 21.2) ~~which-that~~ are moveable against each other in a controlled manner, wherein the sealing elements (21.1, 21.2) are ~~equipped~~ adapted to produce three seams corresponding with the open sides of the bags, and wherein at least some of the sealing elements (21.1, 21.2) of each conveying compartment are simultaneously adjustable to various distances between lateral seams.
14. (Currently Amended) The device according to claim 13, wherein the conveying compartments (3) are positioned in a drum (1) that is rotatable ~~rotating-around~~ a drum axis (A).

15. (Currently Amended) The device according to claim 14, wherein the drum (1) comprises a centrally arranged adjustment device (41), said adjustment device being adapted to ~~equipped for simultaneous adjustment of~~ simultaneously adjust the sealing elements (21.1, 21.2) of all the conveying compartments (3).
16. (Currently Amended) The device according to claim 14, wherein the means (5) for supplying the objects (4) is arranged in the region of an upper zenith of the drum (1), the means for supplying the packaging material (7) or the string of bags is immediately upstream of the means (5) for supplying the objects (4), and the means (9) for discharging the packaged objects (4') are arranged in a lower region of the drum (1).